




2023/09/19 16th Applied Antineutrino Physics workshop

Measurement of reactor neutrinos using plastic scintillator cube

S. Hasegawa¹, T. Konno², T. Kawasaki²




1: Japan Atomic Energy Agency

2; Kitasato University



Plastic Anti-Neutrino Detector Array (PANDA Detector)

Try to measure reactor neutrino




- Scintillator BC-408
- Target volume : ~1 t (1 x 1 x 1m)
- Read out by CAEN 792 (ADC)
- No anti-background material

Tokyo University
 Kitasato University
 Fukui University
 Tokyo Metro University
 Tohoku University 3




Operated by Kansai Electric Power Company (KEPCO)

- Locates at Fukui (Hokuriku area)
- Two reactors restarted from 2018
- Reactor 3 : 1.18MW
- Reactor 4 : 1.18MW



Ohi reactor 4




Experiment at 2019

Measurement of reactor $\bar{\nu}_e$ energy spectrum by On – Off subtraction

- Reactor ON : 38 days (2019.5.28 – 7.4)
→ Neutrino + Back ground
- Reactor OFF : 33 days (2019.7.5 – 8.7)
→ Back ground only

T. Konno ,AAP 2019





- ON,OFF: Accidental subtracted OFF/ON ration; $+0.91 \pm 0.05\%$
- Error of ON -OFF from stat
- IBD events; 177.6 ± 38.7 (/day)
- Compared MC

Succeeded measurement of neutrino spectrum

Next step

- Improvement of reactor neutrino sensitivity
- Reduce Background
- Detection efficiency


- Need to reduce gamma BG



- ✓ Energy separation
 - ⇒ 10 x 10 x 100 cm unit
 - Build to 1m³ unit
- Position separation
 - ⇒ PMT both-ends readout
 - resolution ~20 cm in module
 - difficult to separate positron from annihilation γ
 - ⇒ cannot reduce contingencies
- ✓ n-Gd capture particles are indistinguishable from γ -rays ⇒ environmental γ -rays, etc.


- ✓ High vertex resolution
 - Small scintillator unit
 - ⇒ 2 x 2 x 2 cm module
 - Build to 1m³ unit
 - & SiPM both-ends readout to separate positron from annihilation γ
 - ⇒ delayed coincidence

Start this project from 2022




How to make ?

- ✓ Scintillation material in each grid filling pellets / set cubes
- ✓ Through WLS
- ✓ SiPM readout
- ✓




Pellets scintillator








Detector mockup of about 10 cm

- Plastic scintillator pellets (about 2~3mm)
- Reflective material is the partition plate Furukawa Electric MCPET 0.5mm thick
- 3D readout with WLS fiber Kuraray Y-11 (ϕ 1mm)
- Not SiPM






- principle demonstrator
- 10cm³ (4 × 4 × 4 cells)
 - SiPM readout
 - Light separation
 - e⁺ detection(beam test)






- Observation of light in the same cell
- Confirms positional synchronization measurement on a cell-by-cell.
- Next beam test 64 ch readout



- Next beam test 64 ch readout

JAEA's 5 research reactor

Location	Name		Power (MW)
Tokai	JRR-3	Japan Research Reactor 3	20
	NSRR	Nuclear Safety Research Reactor	0.3
	STACY	Static Experiment Critical Facility	2.E-04
Oarai	HTTR	High Temperature Engineering Test Reactor	30
	JOYO	Fast Breeder Research reactor	100




Pros:

- Detector set in close (~ a few m)
- Short cycle operation (26 days)
- Easier to Obtain operation information in detail
- Easier to access for research

Cons:


- Neutrino source has a finite size near the reactor location
- Low power
- High back ground
- Restriction on installation location

JRR-3
Japan research reactor No.3
20MW



(<https://jrr3.jaea.go.jp/>)

月





$$\text{JRR-3/Ohi: } \left(\frac{20 \text{ MW}}{3000 \text{ MW}} \right) / \left(\frac{3 \text{ m}}{45 \text{ m}} \right)^2 = 1.5$$

10m location; back of 1G BL



3m location; on 3G BL




Gamma spectrum
(Non calibration)



Neutron; He-3
 γ ; NaI,




Shield




5 x 25 x 50cm BPE plates 5 x 10 x 20cm Pb blocks

	No Shield (Hz)	Shield (Hz)
γ	130	5
n	3 - 4	0.02

BG gamma rate @ 3m



BG Neutron rate @ 3m



- Non stable gamma; x 2.4
Neutron x 15
- The rate of γ and neutron tend to synchronize
→ Common source ?
fuel state/ neutron beam ?
- Required to understand the causes of variation for detection efficiency

- ✓ The cause of the time variability of the dose is under investigation.
- ✓ Need to suppression of fluctuation (change of location, add shielding) at JRR-3



Summary



- In Japan, reactor monitors with neutrino IBD signal detection using plastic scintillators have been developing.
- Cell-type detector is developed for the next PANDA. A prototype was assembled and testing.
- Background measurements were performed at the research reactor JRR-3.
- Next, beam test with electron beam for test detector. An investigation of the cause of variation of BG should be conducted.

Thanks!



This work was supported JSPS KAKENHI Grant 22K03654, and JAEA Fund for Exploratory Researches (Houga fund)